

# DMN702G

**MCP Green, emergency door release, double pole free contact, surface mount with glass**

## General

---

The DMN702G is a green manual call point for surface mount applications. It offers double pole, changeover contacts with common, normally open and normally closed connections. It is supplied with a EN54 breakable glass and test key.

## Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

## Options and approvals

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



## Details

---

- Specifically for door security and evacuation
- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

# DMN702G

MCP Green, emergency door release, double pole free contact, surface mount with glass

## Technical specifications

### General

Status indication	Alarm Flag
Compatibility	Conventional detection systems

### Electrical

Cable specification	0.5 to 2.5 mm <sup>2</sup> (termination)
No. of cable cores	2

### Detection

Detection principle	Manual activation
Installation height	Determined by local regulation

### Output

Output type and rating	2A @ 30 VDC (resistive load)
------------------------	------------------------------

### Physical

Net weight	110 g
Colour	Green
Mounting type	Back box
Material (body)	PC / ABS
Functional marking	Running man

### Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

### Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	CE

### Compatible products

Category	Reference	Description
Detection device	DM711	EN54 Universal glass, Aritech branded device
Detection device	DM715	EN54 Universal MCP glass, without branding
Detection device	DM788GR	Surface Mount Box Without Connectors, Green
Detection device	DMN782	Hinged transparent MCP protection cover
Detection device	DMN784	Replacement test key for Manual Call Points, 10 pack
Detection device	DMN787G	Surface mounting box with earth connector, green
Detection device	DMN789	Replacement Pluggable Connectors For Manual Call Points (10 Pack)



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 15 February 2024 - 9:36