

DC-D4811WRX 3.3mm

8MP Vandal-Resistant IR Dome Camera



- 8MP(3840x2160) resolution
- Two-way audio
- PoE (IEEE 802.3af Class 3)
- IR LED (30m / 98.4 ft (4ea))
- Supports ONVIF
- Fixed-focal lens (f=3.3mm)
- Alarm in / out
- Day and night (ICR)
- 3-axis mechanical design for installation
- micro SD/SDHC/SDXC
- IK10 / IP67 supports
- True wide dynamic range (WDR)
- Easy installation with DirectIP NVR

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	3840 x 2160
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	3.3mm
Aperture	F2.0
Iris Control	Fixed Iris
Angular Field of View	101.3° (H) 54.5°(V) 119.7°(D)
Min. Illumination	COLOR: 0.2 lux @ F2.0 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4 ft (4ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Pan/Tilt/Rotate	
Pan Range	-170° ~ 170°
Tilt Range	-5° ~ 67.5°
Rotate Range	-109° ~ 109°
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR/ VBR H.264 - CBR/ VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	30ips : 3840 x 2160 15ips : 3840 x 2160(WDR)
Supported Resolution	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/RTCP/RTSP/HTTP/TCP/RTMP/UDP/RTSP/FTP/HTTP/HTTPS/FTP/SNTP/SMTP/FEN mDNS, uPNP, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1X/EAP-TLS, Chained Fingerprint, SSLEncryption, HTTPSEncryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE (IEEE802.3af Class 3)
Power Consumption	PoE (IEEE802.3af Class 3), 9.0W
Approval	FCC CE KC
Mechanical	
Dimensions	Ø120.6 x 92.9mm (Ø4.75" x 3.66")
Weight	0.48kg (1.06lb)



PRODUCT IMAGE



DIMENSIONS



ACCESSORIES (OPTIONAL)

DA-JB4700	DA-MA4300	DA-WM2050	DA-CM2050
JUNCTION BOX	MOUNT ADAPTER	WALL MOUNT	CEILING MOUNT
DA-LM2000	DA-RM2000	DA-JB4600	
Pole Mount	Corner Mount	JUNCTION BOX	

ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-D4811WRX 3.3mm	WALL	 JUNCTION BOX Model:DA-JB4700
		or
		 MOUNT ADAPTER Model:DA-MA4300
		+
		 WALL MOUNT Model:DA-WM2050
	CELLING	 JUNCTION BOX Model: DA-JB4700
		or
		 MOUNT ADAPTER Model: DA-MA4300
		+
		 CEILING MOUNT Model: DA-CM2050
	POLE	 MOUNT ADAPTER Model: DA-MA4300
		+
		 WALL MOUNT Model: DA-WM2050
		+
		 POLE MOUNT Model: DA-LM2000
		or
		 JUNCTION BOX Model: DA-JB4700
		+
		 POLE MOUNT Model: DA-LM2000
		or
		 JUNCTION BOX Model: DA-JB4600
		+
		 POLE MOUNT Model: DA-LM2000
	CORNER	 MOUNT ADAPTER Model:DA-MA4300
		+
		 WALL MOUNT Model:DA-WM2050
		+
		 CORNER MOUNT Model:DA-RM2000
		or
		 JUNCTION BOX Model:DA-JB4700
		+
		 CORNER MOUNT Model:DA-RM2000
		or
		 JUNCTION BOX Model:DA-JB4600
		+
		 CORNER MOUNT Model:DA-RM2000