

# TX-1011-03-1

**Slimline door/window sensor 868 MHz, Gen2, white**

## Installation

---

This wireless sensor protects anything that opens and closes such as doors, windows and cabinets by means of internal reed switches. You can also choose to use the transmitter to monitor a supervised contact. The sensor is equipped with a wall and cover tamper for additional security.



## Details

---

- Learn-mode technology
- Supervised transmissions
- More than 3 years battery life
- Complies with EN50131-5-3 - approvals pending

# TX-1011-03-1

Slimline door/window sensor 868 MHz, Gen2, white

## Technical specifications

---

### General

Application type	Surface mount
------------------	---------------

### Wired / wireless

Wired-wireless	Wireless
Wireless frequency	868 MHz
Open-air range	400 m
Operating gap	10 mm max.

### Electrical

Batteries	1 x 3 V Lithium
Battery lifetime	3 to 5 years

### Physical

Dimensions contact / sensor	102 x 32 x 32 mm
Colour	White

### Regulatory

EN50131 grade	Grade 2
Certification	EN50131, F&P, INCERT, REQ



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 5 May 2023 - 9:32