

# PM812N-G3

### Power supply, Switch Mode, 13.8 VDC, 1.5 A, EN Grade 3

#### **EN** certified

Suitable for use in systems designed to comply with EN50131-6:2008 Grade 3 and Environmental Class II requiring 18Ah standby battery capacity.

#### **Protection**

Comprehensive protection is built-in as standard including mains transient filtering, electronic output overload protection and fuses on the load and battery outputs.



#### **Details**

- · Intelligent active battery monitoring
- Fault signals for loss of mains, battery fail and power supply fault
- Battery deep discharge protection
- Tamperswitch
- Protection against reverse battery connection
- Electronic overload protection
- LED's for comprehensive diagnostics
- Powder coated steel housing
- EN50131-6:2008 grade 3 certified

# PM812N-G3

## Power supply, Switch Mode, 13.8 VDC, 1.5 A, EN Grade 3

### **Technical specifications**

General	
Fuse(s)	Load: F1.6 A, Batt: F1.6 A
Deep discharge protection	Battery disconnect @ 10.5 V battery terminal voltage
Protection	Reverse battery connection protection
Electrical	
Mains input	100 to 240 VAC
Output	
Power output voltage	13.8 VDC
Output ripple	<400 mV pk-pk max. @ rated voltage
Power output current mains	1.5 A
Battery	
Max. Battery capacity	18 Ah 12 V
Power output current	12 h, 1.5 A with 18 Ah battery / 30 h, 0.6 A with
battery	18 Ah battery
Battery recharge time	<24 h to 80%
Physical	
Physical dimensions	330 x 275 x 80 mm (W x H x D)
Net weight	3.3 kg (without battery)
Colour	White
Form factor	Steel cabinet
Housing (steel) powder coated	1.2 mm
Environmental	
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Regulatory	
EN50131 Grade	Grade 3
Compliancy	CE, REACH, RoHS 2, WEEE
Certification	EN50131 Grade 3
Certification	EN50131-6:2008 Grade 3 Type A
	Environmental Class II



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.