

# PM811N-G2

### Power Supply Switch Mode, 12 VDC, 1 A, EN Grade 2

#### Certified Gr.2

Suitable for use in systems designed to comply with EN50131-6:2008 Grade 2 and Environmental Class II requiring 8 Ah standby battery capacity.

#### **Protection**

Comprehensive protection is built-in as standard including mains transient filtering, electronic output overload protection and fuses on the load and battery outputs.



#### **Details**

- Fault signals for loss of mains, power supply fault and battery low voltage warning
- Battery deep discharge protection
- Tamperswitch
- Protection against reverse battery connection
- LED's for comprehensive diagnostics
- Thermal protection of power circuitry
- Powder coated steel housing
- EN50131-6:2008 Grade 2 Type A certified

# PM811N-G2

## Power Supply Switch Mode, 12 VDC, 1 A, EN Grade 2

### **Technical specifications**

General	
Fuse(s)	Load: F1.0 A, Batt: F1.0 A
Deep discharge protection	Battery disconnect @ 10.6 V battery terminal voltage
Protection	Reverse battery connection protection
Electrical	
Mains input	100 to 240 VAC
Output	
Power output voltage	13.8 VDC
Output ripple	<400 mV pk-pk max. @ rated voltage
Power output current mains	1 A
Battery	
Max. Battery capacity	8 Ah, 12 V
Power output current battery	12 h, 0.6 A with 8 Ah battery
Battery recharge time	<72 h to 80%
Physical	
Physical dimensions	230 x 200 x 80 mm (W x H x D)
Net weight	2 kg (without battery)
Colour	White
Form factor	Steel cabinet
Housing (steel) powder coated	1.2 mm
Environmental	
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Environment	EN50130-5 ; Class II - Indoor (general)
Regulatory	
EN50131 Grade	Grade 2
Compliancy	CE, REACH, RoHS 2, WEEE
Certification	EN50131 Grade 2
Certifications	EN50131-6:2008 Grade 2 Type A



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.