

DC-T4517WRXP 4.3mm

H.265 5MP PoE Extender Bullet Camera



- 5MP (2592x1944) resolution
- PoE, IEEE 802.3at(Class 4), Built-in PoE Extender
- Easy installation with DirectIP NVR
- IR LED (20 m / 65.6 ft (2 ea))
- Day and night (ICR)
- H.265 and Intelligent Codec
- Fixed-focal lens
- True wide dynamic range (WDR)
- Supports ONVIF

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	4.3mm
Aperture	F1.6
Iris Control	Fixed Iris
Angular Field of View	4:3 mode : 80°(H) 56.7°(V) 106.9°(D) 16:9 mode : 80°(H) 41.1°(V) 95.4°(D)
Min. Illumination	COLOR: 0.15 lux @ F1.6 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	20 m / 65.6 ft (2 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR/ VBR H.264 - CBR/ VBR
Audio Compression	-
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960x 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/RTCP/RTSP/HTTP/TCP/RTMP/UDP/RTSP/TCP/HTTP/HTTPS/FTP/SNTP/SMTP/FEN mDNS, Upnp, SNMPv2
Security	Digest authentication, Password Protection, User accesslog, IP Filtering, IEEE802.1X/APS/TLS, Chained Fingerprint, SSLEncryption, HTTPSEncryption
Ethernet	1 RJ45(10/100BASE-T), 1 Additional RJ45(10/100BASE-T) for PoE Extender
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Alarm and Event	
Trigger Event	Motion Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE IEEE802.3at(Class 4)
Power Consumption	PoE IEEE802.3at(Class 4), 25.5W (DC OUT : 42.5-57V=, 0.3A MAX)
Approval	FCG CE KC
Mechanical	
Dimensions	70mm X 65mm X 197.5mm (2.76" X 2.56" X 7.78")
Weight	0.44kg (0.97lb)



PRODUCT IMAGE



DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



Pole Mount

Junction Box

Corner Mount

ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION	
DC-T4517WRXP 4.3mm	POLE	 POLE MOUNT Model: DA-LM2000	
			 JUNCTION BOX Model: DA-JB2400
	CORNER	 CORNER MOUNT Model:DA-RM2000	
			 JUNCTION BOX Model:DA-JB2400