

DC-E4216WRX

Full HD IR Bullet Camera



- Easy installation with DirectIP NVR
 - micro SD/SDHC/SDXC
 - IK10 / IP67 supports
 - True wide dynamic range (WDR)
 - Supports ONVIF
- Full HD (1080p) resolution
 - Two-way audio
 - PoE (IEEE 802.3af Class 2)
 - IR LED (30m / 98.4 ft (4 ea))
- Fixed-focal lens (f=2.8mm)
 - Alarm in / out
 - Day and night (ICR)
 - 3-axis mechanical design for installation

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f=2.8mm
Aperture	F 2.0
Iris Control	Fixed Iris
Angular Field of View	111.6°(H), 61.45°(V), 127.3°(D)
Min. Illumination	COLOR : 0.1 lux @ F2.0 B/W : 0 lux (IR LED ON)
S/N Ratio	More than 45dB
Dynamic Range	120dB
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	IR cut filter with auto switch
IR Distance (LEDs)	30m / 98.4 ft (4 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	On / Off
Mirroring / Pivot	Horizontal / Vertical / Pivot
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Network	
Video Compression	H.265, H.264 (MP) M-JPEG,
Intelligent Codec	Supported
Video Compression Level (Quality)	Basic, Standard, High, Very High
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	30ips : 1920 x 1080(WDR)
Supported Resolution	1920x1080, 1280x720, 640x360, 352x240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x ,IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Audio Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio In/ Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Material	Metal
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F), Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE (IEEE 802.3af Class 2)
Power Consumption	PoE, IEEE 802.3af (Class 2), 6.1W
Approval	FCC, CE, KC
Mechanical	
Dimensions (W x H)	75mm x 70mm x 195.8mm (2.95" x 2.75" x 7.7")
Weight	0.655 kg



PRODUCT IMAGE



ACCESSORIES (OPTIONAL)

DA-JB4150	DA-JB2400	DA-LM2000	DA-RM2000
Junction Box	Junction Box	Pole Mount	Corner Mount

ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-E4216WRX	WALL	 JUNCTION BOX Model:DA-JB4150
		or
		 JUNCTION BOX Model:DA-JB2400
	CELLING	 JUNCTION BOX Model: DA-JB4150
		or
		 JUNCTION BOX Model: DA-JB2400
	POLE	 JUNCTION BOX Model: DA-JB4150
		+
		 POLE MOUNT Model: DA-LM2000
		or
		 POLE MOUNT Model: DA-LM2000
		+
		 JUNCTION BOX Model: DA-JB2400
	CORNER	 CORNER MOUNT Model:DA-RM2000
		+
		 JUNCTION BOX Model:DA-JB2400
		or
		 JUNCTION BOX Model:DA-JB4150
		+
		 CORNER MOUNT Model:DA-RM2000