

4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors



- 4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors
- 5MP CMOS
- 5MP @ 20fps 4-in-1 video output switch
- 2.7 ~ 13.5 mm motor lens with autofocus (92.3 ° ~ 29.3 °)
- ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, motion detection and privacy masks
- IP67 3AXIS
- 12V DC, 24V AC.



Reference / Model	HYU-757 / SF-DM855UZW-Q4N1
5 MP CMOS	
5MP (2560x1944) at 20 fps	
Ultra low lighting	
2.7 ~ 13.5 mm motorized lens with autofocus	
OSD menu control via coaxial cable (UTC)	
WDR 130dB, 3D-DNR	
Smart IR up to 60 meters	
4-in-1 video output	
IP67	
Specs	
5 MP CMOS sensor	
Digital resolution: 5MP (2560x1944)	
Frames per second:	

4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors

Reference / Model	HYU-757 / SF-DM855UZW-Q4N1
TVI: 5MP (20 fps), 4MP (25/30 fps), 1080P (25/30 fps)	
AHD: 5MP (20 fps), 4MP (25/30 fps)	
CVI: 4MP (25/30 fps)	
CVBS: PAL / NTSC	
4-in-1 video output switch (HDCVI, HDTVI, AHD, CVBS)	
Removable mechanical filter	
0.003 lux F1.2 (color) / 0 lux IR On	
Smart IR: 60 meters	
2.7 ~ 13.5 mm motorized lens with autofocus	
Viewing angle of 92.3 ° ~ 29.3 ° (H)	
Auto and manual white balance	
Automatic gain control	
Backlight Compensation: BLC	
WDR 130dB	
3D digital noise reduction	
4 programmable video sensor	
4 programmable privacy masks	
Brightness and sharpness adjustment	
Mirror mode	
Power supply: 12V DC (± 20%), 24V AC (± 20%)	
Consumption: Max. 10.5W	
Operating temperature of -40 ° C ~ + 60 ° C	
Relative humidity: <90% (no condensation)	
IP67	
Metalcase	
Dimensions: 123.86 (W) x 110.24 (H) x 134.3 mm	

4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors

Reference / Model	HYU-757 / SF-DM855UZW-Q4N1
Weight: 630 g	
3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 360 ° (Rotation)	