

# DH-2010P

## DirectIP® PoE Switch



- Individual port for data transmission to DirectIP® NVR
- Central power control for greater network utility
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Supports 10 RJ45 ports
- Maximum per-device PoE delivery of 70W available for 1~8 RJ45 ports

### SPECIFICATIONS

| System                 |                                                      |
|------------------------|------------------------------------------------------|
| CPU                    | Embedded MIPS                                        |
| System Memory          | 256MB SDRAM, 32MB Flash                              |
| Switching Capacity     | 5.6Gbps                                              |
| Connectivity           |                                                      |
| Copper Service Port    | 8 RJ45 Connectors (10/100BASE-T)                     |
| Copper Uplink Port     | 2 RJ45 Connectors (10/100/1000BASE-T)                |
| Optical Uplink Port    | none                                                 |
| PoE Power              |                                                      |
| supported Standards    | IEEE 802.3af-2003 / IEEE 802.3at-2009                |
| PD Connection          | Up to 8 IEEE 802.3af PDs or up to 2 IEEE 802.3at PDs |
| PSE Power Budget       | 70W                                                  |
| General                |                                                      |
| Diemensions(W x H x D) | 280mm x 44mm x 180mm (11.0" x 1.7" x 7.1")           |
| Weight                 | 1.35Kg (2.97lb)                                      |
| Operation Temperature  | 0°C ~ 40°C (32°F ~ 104°F)                            |
| Power Input            | AC100-240V, 2.0~1.0A, 50/60Hz                        |
| Power Consumption      | 90W                                                  |
| Approvals              | FCC,CE,KC,UL,CB                                      |



### PRODUCT IMAGE



### DIMENSIONS



