

HYU-414N

SF-IPB025H-2E / SF-IPB025HG-2E

HYUNDAI

HYUNDAI NEXT GEN 1080P SMART IR IP CAMERA 30M IP67



- HYUNDAI Next Gen IP bullet camera with Smart IR 30m for outdoors
- 1 / 2.7 "CMOS of 2MP
- Dual stream
- H.265, H.264 and MJPEG compression formats
- Resolution up to 1080P at 25ips
- ICR filter
- 0.01 lux F2.0
- 2.8 mm (112 °) fixed lens
- OSD, AWB, AGC, BLC, digital WDR, 3D-DNR, ROI, video sensor and privacy masks
- Onvif, ISAPI
- IP67
- 3AXIS
- 12V DC
- Supports PoE



Reference / Model	HYU-414N / SF-IPB025H-2E / SF-IPB025HG-2E
Specifications	

HYUNDAI NEXT GEN 1080P SMART IR IP CAMERA 30M IP67

Reference / Model

HYU-414N / SF-IPB025H-2E / SF-IPB025HG-2E

Image Sensor 1 / 2.7 "2 Megapixel CMOS
Resolution: 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)
H.265, H.264 and MJPEG video compression
Stream 1: 1080P, 720P (25 ips)
Stream 2: VGA, Q720P (25 ips)
Day / night mode with removable mechanical filter (ICR)
0.01 lux F2.0 (color), 0 lux IR On
Smart IR: 30 meters
2.8mm fixed lens
Viewing angle: 112.1 ° (H), 60 ° (V), 132.2 ° (D)
Imaging Modes: BLC, Digital WDR, 3D-DNR
Image settings: Saturation, brightness, contrast, sharpness, gain and white balance adjustable through client software or web browser
Supports video sensor, 1 region of interest (ROI) in main stream and privacy mask
Network interface: RJ45 (10 / 100M) self-adaptive
Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL / TLS
Remote viewing with IE10 + browsers (requires plug-in), Chrome 57.0+, Firefox 52.0+ and IOS and Android smartphone
ONVIF and ISAPI compliant
DDNS compliant
Up to 32 users
Up to 6 simultaneous views
Power supply: 12V DC (± 25%)
Consumption: 5W, 6.5W PoE
Supports PoE (802.3 af, Class 3)
-30 ° C ~ + 60 ° C operating temperature
Humidity: <95% (non-condensing)
Degree of protection IP67
Metal and plastic housing
Dimensions: 67.8 (W) x 66.2 (H) x 177.6mm
Weight: 270g
3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 180 ° (TILT), 0 ° ~ 360 ° (Rotation)