

WI-IOT110

Wi-Tek



Wi-Tek WI-IOT110. Router 4G M2M LTE industrial Wi-Tek. 2 SMA 4G antennas. 2 Fast Ethernet LAN ports with PoE output. 1 Fast Ethernet WAN port with PoE input. PoE delivery up to 60W. Modbus TCP/IP protocol. Layer 2 Manageable in the cloud. OpenVPN compatible. DIN rail mounting Wi-iot110.

- Wi-Tek Industrial M2M LTE Router
- Designed to provide M2M/IoT application solutions for most areas.
- Up to 150 Mbps download speed and 50 Mbps upload speed
- Compatible with 4G/3G networks
- 4G Internet access, no configuration required, just plug and play
- Free cloud management platform simplifies equipment management time and reduces network monitoring costs
- L2's robust management features meet the requirements of complex projects and can be deployed in one go without the need to invest in additional devices
- Compatible with Microsoft Azure and AWS (Amazon Web Services)
- WiFi Antennas: 2 SMA 4G, 2 SMA
- 2 10/100M Ethernet LAN ports (48V 12+ 36- PoE output)
- 1 10/100M Ethernet WAN port (PoE input 15/30/60W)
- PoE delivery: max 60W
- Hardware Watchdog
- Network protocols: TCP, UDP, IPv4, ICMP, ICMP, NTP, DHCP, DNS, HTTP, HTTPS, ARP, PPPoE, UPNP, SSH, Telnet, SNMP, TFTP, MQTT
- Supports dry contact input and 3.3 V output
- Supports OpenVPN, allowing you to remotely connect to your main office with the same security as in the office
- WAN backup connection: Functions as a router to provide a backup Internet connection
- Connectors: 1 DC, 3 Ethernet, 2 Mobile SMA, 2 WiFi RP-SMA, 1 DB9 female (RS232), 1 Terminal (RS485/RS422)
- Support for an external SIM card
- PoE outputs: allows direct use of a network cable to transmit data and supply power to the camera at the same time

- Power supply: 48V ~ 60V DC (2-pin DC connector)
- Operating temperature: -30°C ~ +65°C (-30°C ~ +65°C)
- Dimensions: 45 (W) x 145 (H) x 95 mm
- Net weight: 500 g
- Supports DIN rail mounting

- WITEK-0094

